

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

febi 24704 hydraulic fluid
Article number: 24704

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Hydraulics oil

1.2.2 Uses advised against

For all uses not specified in SECTION 1.2.1

1.3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG
Wilhelmstr. 47
58256 Ennepetal / GERMANY
Phone +49 2333 911-0
Fax +49 2333 911-444
Homepage www.febi.com
E-mail info@febi.com

Address enquiries to

Technical information info@febi.com

Safety Data Sheet info@febi.com

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (english)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Skin Irrit. 2: H315 Causes skin irritation.
Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

The product is required to be labelled in accordance with regulation (EC) No 1272/2008 (CLP).

Hazard pictograms



Signal word

WARNING

Hazard statements

H315 Causes skin irritation.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P280 Wear protective gloves / protective clothing.
P332+P313 If skin irritation occurs: Get medical advice / attention.
P501 Dispose of contents / container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Special labelling

Contains: 3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, Tolutriazol Derivate. EUH208 May produce an allergic reaction.

2.3 Other hazards

none

Environmental hazards

Does not contain any PBT or vPvB substances.

Other hazards

Further hazards were not determined with the current level of knowledge.

SECTION 3: Composition / Information on ingredients

Product-type:

The product is a mixture.

Range [%]	Substance
30 - < 60	Distillates (petroleum), hydrotreated light naphthenic
	CAS: 64742-53-6, EINECS/ELINCS: 265-156-6, EU-INDEX: 649-466-00-2
	GHS/CLP: Asp. Tox. 1: H304
15 - < 30	Distillates (petroleum), hydrotreated light paraffinic
	CAS: 64742-55-8, EINECS/ELINCS: 265-158-7, EU-INDEX: 649-468-00-3, Reg-No.: 01-2119487077-29-xxxx
	GHS/CLP: Asp. Tox. 1: H304
15 - < 25	Distillates (petroleum), hydrotreated middle
	CAS: 64742-46-7, EINECS/ELINCS: 265-148-2, EU-INDEX: 649-221-00-X
	GHS/CLP: Acute Tox. 4: H332 - Asp. Tox. 1: H304 - Skin Irrit. 2: H315 - Aquatic Chronic 2: H411
5 - < 15	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based
	CAS: 72623-87-1, EINECS/ELINCS: 276-738-4, EU-INDEX: 649-483-00-5
	GHS/CLP: Asp. Tox. 1: H304
< 1	2,6-di-tert-butylphenol
	CAS: 128-39-2, EINECS/ELINCS: 204-884-0, Reg-No.: 01-2119490822-33-XXXX
	GHS/CLP: Skin Irrit. 2: H315 - Aquatic Chronic 1: H410 - Aquatic Acute 1: H400
< 1	Tolutriazol Derivate
	EINECS/ELINCS: 939-700-4, Reg-No.: 01-2119982395-25-XXXX
	GHS/CLP: Skin Irrit. 2: H315 - Skin Sens. 1: H317 - Aquatic Acute 1: H400 - Aquatic Chronic 2: H411
< 1	3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid
	CAS: 268567-32-4, EINECS/ELINCS: 434-070-2, Reg-No.: 01-2119658068-31-XXX
	GHS/CLP: Eye Dam. 1: H318 - Skin Sens. 1: H317 - Aquatic Chronic 3: H412

Comment on component parts

Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.
 For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Take off contaminated clothing and wash before reuse.

Inhalation

Ensure supply of fresh air.
 In the event of symptoms seek medical treatment.

Skin contact

When in contact with the skin, clean with soap and water.
 Consult a doctor if skin irritation persists.

Eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If eye irritation persists: Get medical advice/attention.

Ingestion

Seek medical advice immediately.
 Do not induce vomiting.
 Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
 If swallowed or in the event of vomiting, risk of product entering the lungs.
 Forward this sheet to the doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media	Foam, dry powder, water spray jet, carbon dioxide.
Extinguishing media that must not be used	Full water jet.

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.
Carbon monoxide (CO)
Sulphur oxides (SO_x).

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.
Use self-contained breathing apparatus.
Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.
Forms slippery surfaces with water.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).
Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. general-purpose binder).
Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid formation of aerosols.
Fire class (DIN EN 2): B
Do not smoke.
Do not eat, drink or smoke when using this product.
Wash hands before breaks and after work.
Cloths contaminated with product should not be kept in trouser pockets.
Use barrier skin cream.
Contaminated work clothing should not be allowed out of the workplace.
Take off contaminated clothing and wash before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.
Prevent penetration into the ground.
Do not store together with oxidizing agents.
Do not store together with food and animal food/diet.
Keep container tightly closed.

7.3 Specific end use(s)

See product use, SECTION 1.2

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Substance
Distillates (petroleum), hydrotreated light paraffinic
CAS: 64742-55-8, EINECS/ELINCS: 265-158-7, EU-INDEX: 649-468-00-3, Reg-No.: 01-2119487077-29-xxxx
Long-term exposure: 5 mg/m ³ , ACGIH TLV (OIL MIST)

DNEL

Substance
2,6-di-tert-butylphenol, CAS: 128-39-2
Industrial, dermal, Long-term - systemic effects: 11,25 mg/kg bw/day.
Industrial, inhalative, Long-term - systemic effects: 70,61 mg/m ³ .
general population, oral, Long-term - systemic effects: 6,75 mg/kg bw/day.
general population, inhalative, Long-term - systemic effects: 20,9 mg/m ³ .
3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4
Industrial, inhalative, Long-term - systemic effects: 2,4 mg/m ³ (AF=75).
general population, oral, Long-term - systemic effects: 0,2 mg/kg bw/d (AF=600).
general population, dermal, Long-term - systemic effects: 0,2 mg/kg bw/d (AF=600).
general population, inhalative, Long-term - systemic effects: 0,6 mg/m ³ (AF=150).
Tolutriazol Derivate
Industrial, dermal, Long-term - systemic effects: 0,4 mg/kg bw/d.
Industrial, inhalative, Long-term - systemic effects: 1,3 mg/m ³ .
general population, inhalative, Long-term - systemic effects: 0,3 mg/m ³ .
general population, oral, Long-term - systemic effects: 0,2 mg/kg bw/d.
general population, dermal, Long-term - systemic effects: 0,2 mg/kg bw/d.

PNEC

Substance
2,6-di-tert-butylphenol, CAS: 128-39-2
soil, 0,063 mg/kg soil dw.
sediment (seaater), 0,032 mg/kg sediment dw.
sediment (freshwater), 0,317 mg/kg sediment dw.
sewage treatment plants (STP), 10 mg/l.
seawater, 0,00 mg/l.
freshwater, 0,001 mg/l.
oral (food), 60 mg/kg food.
3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4
soil, 2,39 mg/kg dw.
freshwater, 0,038 mg/l.
seawater, 0,0038 mg/l.
sewage treatment plants (STP), 10 mg/l.
sediment (freshwater), 12,1 mg/kg dw.
sediment (seaater), 1,21 mg/kg dw.
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
oral (food), 9,33 mg/kg food.
Tolutriazol Derivate
freshwater, 0,000976 mg/l.

sewage treatment plants (STP), 0,69 mg/l.
seawater, 0,0000976 mg/l.

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances. General exposure limit for oil mist should be noted.
Eye protection	If there is a risk of splashing: Safety glasses. (EN 166:2001)
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. > 0,11 mm: Nitrile rubber, >480 min (EN 374-1/-2/-3).
Skin protection	Light protective clothing.
Other	Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier. Avoid contact with eyes and skin.
Respiratory protection	Breathing apparatus in the event of aerosol or mist formation. Short term: filter apparatus, combination filter A-P1. (DIN EN 14387)
Thermal hazards	No information available.
Delimitation and monitoring of the environmental exposition	See SECTION 6+7.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	liquid
Color	green-yellow
Odor	characteristic
Odour threshold	not determined
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point [°C]	No information available.
Flash point [°C]	> 90 (ISO 2592)
Flammability (solid, gas) [°C]	No information available.
Lower explosion limit	No information available.
Upper explosion limit	No information available.
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	< 0,01 (20°C)
Density [g/ml]	~0,86 (DIN 51757) (15 °C / 59,0 °F)
Bulk density [kg/m³]	not applicable
Solubility in water	immiscible
Partition coefficient [n-octanol/water]	not determined
Viscosity	~ 21 mm²/s (40°C) (DIN 51562/T1)
Relative vapour density determined in air	not determined
Evaporation speed	not determined
Melting point [°C]	~-51 (ISO 3016)
Autoignition temperature [°C]	not determined
Decomposition temperature [°C]	> 300

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

10.4 Conditions to avoid

Strong heating, because the thermal decomposition starts from > 300°C.

10.5 Incompatible materials

Oxidizing agent

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product
oral, Based on the available information, the classification criteria are not fulfilled.:
inhalative, Based on the available information, the classification criteria are not fulfilled.:
dermal, Based on the available information, the classification criteria are not fulfilled.:
Substance
Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6
LD50, dermal, Rabbit: > 2000 mg/kg.
LD50, oral, Rat: > 5000 mg/kg.
2,6-di-tert-butylphenol, CAS: 128-39-2
LD50, oral, Rat: >5000 mg/kg bw (OECD 401).
LD0, dermal, Rat: > 36 ml/kg bw (Lit.).
3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4
LD50, dermal, Rat: > 2000 mg/kg bw.
LD50, oral, Rat: > 2000 mg/kg bw.
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
LD50, dermal, Rabbit: >= 2000 mg/kg (OECD 402).
LD50, oral, Rat: >= 5000 mg/kg (OECD 401).
LC50, inhalative, Rat: >= 5,53 mg/l (OECD 403).
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
LD50, oral, Rat: >5000 mg/kg bw (OECD 401).
LD50, dermal, Rabbit: >2000 mg/kg bw (OECD 402).
Tolutriazol Derivate
LD50, oral, Rat: > 2000 mg/kg.

Serious eye damage/irritation	Based on the available information, the classification criteria are not fulfilled.
Skin corrosion/irritation	Toxicological data of complete product are not available. Irritant Calculation method
Respiratory or skin sensitisation	Toxicological data of complete product are not available. May produce an allergic reaction. Calculation method
Specific target organ toxicity — single exposure	Based on the available information, the classification criteria are not fulfilled.
Specific target organ toxicity — repeated exposure	Based on the available information, the classification criteria are not fulfilled.
Mutagenicity	Based on the available information, the classification criteria are not fulfilled.
Reproduction toxicity	Based on the available information, the classification criteria are not fulfilled.
Carcinogenicity	Based on the available information, the classification criteria are not fulfilled.
Aspiration hazard	Based on the available information, the classification criteria are not fulfilled.
General remarks	

Toxicological data of complete product are not available.
 The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists.

SECTION 12: Ecological information

12.1 Toxicity

Substance
2,6-di-tert-butylphenol, CAS: 128-39-2
LC50, (21d), Daphnia magna: 0,23 mg/l (OECD 211).
LC50, (48h), Daphnia magna: 0,45 mg/l (US EPA TSCA).
LC50, (96h), Pimephales promelas: 1,4 mg/l (OECD 204).
EC50, (24h), Pseudokirchneriella subcapitata: 2,3 mg/l (US EPA 797.1050).
3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4
LC50, (96h), fish: 54 mg/l.
EC50, (48h), Daphnia magna: 53 mg/l.
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
LC50, (96h), fish: > 100 mg/l (OECD 203).
EC50, (48h), Crustacea: > 100 mg/l (OECD 202).
ErC50, (72h), Algae: > 100 mg/l (OECD 201).
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8
EL50, (24h), Daphnia magna: >10000 mg/l (OECD 202).
LL50, (96h), Pimephales promelas: >100 mg/l (OECD 203).
NOEL, (21d), Daphnia magna: >10 mg/l (OECD 211).
NOEL, (72h), Pseudokirchneriella subcapitata: >100 mg/l (OECD 201).
Tolutriazol Derivate
LC50, (96h), fish: 1,3 mg/l.
EC50, (72h), Algae: 0,976 mg/l.
EC50, (48h), Daphnia magna: 2,05 mg/l.

12.2 Persistence and degradability

Behaviour in environment compartments	not determined
Behaviour in sewage plant	not determined
Biological degradability	not determined

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Other adverse effects

Ecological data of complete product are not available.

Do not discharge product unmonitored into the environment or into the drainage.

The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Coordinate disposal with the disposal contractor/authorities if necessary.
Disposal in an incineration plant in accordance with the regulations of the local authorities.
In according to RoHS!

Waste no. (recommended)

130205* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.
Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended)

150110*

SECTION 14: Transport information

14.1 UN number

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to ADR/RID NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

Marine transport in accordance with IMDG NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

Ferdinand Bilstein GmbH + Co. KG

Date printed 16.11.2017, Revision 15.11.2017

Version 10. Supersedes version: 09 Page 10 / 11

14.4 Packing group

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.5 Environmental hazards

Transport by land according to ADR/RID no

Inland navigation (ADN) no

Marine transport in accordance with IMDG no

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS	1991/689 (2001/118); 2010/75; 2004/42; 648/2004; 1907/2006 (REACH); 1272/2008; 75/324/EEC (2008/47/EC); (EU) 2015/830; (EU) 2016/131; (EU) 517/2014
TRANSPORT-REGULATIONS	DOT-Classification, ADR (2017); IMDG-Code (2017, 38. Amdt.); IATA-DGR (2017).
NATIONAL REGULATIONS (GB):	EH40/2005 Workplace exposure limits (Second edition, published December 2011).
- Observe employment restrictions for people	Observe employment restrictions for mothers-to-be and nursing mothers. Observe employment restrictions for young people.
- VOC (2010/75/CE)	0%

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 Hazard statements (SECTION 03)

H410 Very toxic to aquatic life with long lasting effects.
H400 Very toxic to aquatic life.
H412 Harmful to aquatic life with long lasting effects.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H411 Toxic to aquatic life with long lasting effects.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H304 May be fatal if swallowed and enters airways.

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
ATE = acute toxicity estimate
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging
DMEL = Derived Minimum Effect Level
DNEL = Derived No Effect Level
EC50 = Median effective concentration
ECB = European Chemicals Bureau
EEC = European Economic Community
EINECS = European Inventory of Existing Commercial Chemical Substances
ELINCS = European List of Notified Chemical Substances
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50 = Inhibition concentration, 50%
IMDG = International Maritime Code for Dangerous Goods
IUCLID = International Uniform Chemical Information Database
LC50 = Lethal concentration, 50%
LD50 = Median lethal dose
LC0 = lethal concentration, 0%
LOAEL = lowest-observed-adverse-effect level
MARPOL = International Convention for the Prevention of Marine Pollution from Ships
NOAEL = No Observed Adverse Effect Level
NOEC = No Observed Effect Concentration
PBT = Persistent, Bioaccumulative and Toxic substance
PNEC = Predicted No-Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
STP = Sewage Treatment Plant
TLV@/TWA = Threshold limit value – time-weighted average
TLV@STEL = Threshold limit value – short-time exposure limit
VOC = Volatile Organic Compounds
vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Skin Irrit. 2: H315 Causes skin irritation. (Calculation method)
Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects. (Calculation method)

Modified position

SECTION 2 been added: H315 Causes skin irritation.
SECTION 2 been added: Skin Irrit. 2
SECTION 2 deleted: P273 Avoid release to the environment.
SECTION 2 been added: H412 Harmful to aquatic life with long lasting effects.
SECTION 2 been added: Aquatic Chronic 3
SECTION 2 deleted: Aquatic Chronic 2
SECTION 2 deleted: H411 Toxic to aquatic life with long lasting effects.
SECTION 14 been added: no dangerous goods
SECTION 14 deleted: Environmentally hazardous substance, liquid, n.o.s. (Distillates (petroleum), hydrotreated middle)